

Description

A one-component metallic lacquer in aerosol form that has been specially conceived to be applied over Zinga. The dried film contains a high percentage of aluminium pigments and a low percentage of acrylic resins.

Outstanding Characteristics

- Provides an outstanding bright aluminium finish which does not have the appearance of a paint.
- Considerably enhances the lifespan of the Zinga corrosion protection.
- Provides enhanced mechanical protection to the Zinga coating.
- Easy to apply through the use of standard aerosol.

Typical Uses

To improve the aesthetic appearance of a Zinga coating over a small area.

Physical Data

Finish	Satin
Colour	Aluminium
Substrate	Zingaised steel
Components	1
Curing mechanism	Solvent evaporation
Propellant	Butane/propane
Viscosity	18 secs DIN Ford 4
<i>Theoretical Coverage:</i>	
Spraying	7m ² /aerosol @ 20µm
<i>Drying Times @ 20°C:</i>	
Touch Dry	5-10 mins
Dry for exposure to rain	1 hr
Flash Point	<0°C
Minimum application temp.	5°C
Minimum working temp.	-20°C
Thinner	N/A
Cleaner	Zingasolv/Gunwash
Application methods	Aerosol
Pot life	N/A
Shelf life	Unlimited
<i>Packing size:</i>	
Aerosols	500ml
Storage	Aluspray cans should always be stored at room temperature on their side, away from direct sun light and sources of ignition.